



Cleaning Agent 761.6

Hot melt material to clean melting units, hoses, and application units in which reactive PUR hot melt adhesives are processed.

Fields of application

- Cleaning of melting and application units with replaceable reactive PUR hot melt adhesive inserts, and other non-reactive hot melt adhesive systems (e. g. those based on EVA)

Advantages

- The use of a hot melt cleaning agent prevents clogging of feeding systems as well as reactive incrustation on application units. Renders nozzles clog free.
- Good mixing characteristics with PUR adhesives
- Blocks the isocyanate reaction
- The same processing temperature as KLEIBERIT PUR hot melt adhesives

Properties of the hot melt cleaning agent

Base:	EVA Copolymers
Specific gravity:	approx. 0.9 g/cm ³
Colour:	blue
Viscosity Brookfield HBTD, sp. 27/10 rpm:	at 100°C: approx. 18.000 mPa · s at 120°C: approx. 8.000 mPa · s at 140°C: approx. 5.000 mPa · s
Supplied as:	Granules
Identification:	Identification not required according to the German hazardous substances regulations GefStoffV, (see our safety data sheet)

Attention:

When hot melt adhesives are melted and applied, vapours are set free and an unpleasant odour can occur, even if the recommended working temperature has been observed. Moreover if the prescribed working temperature is exceeded over a longer period, harmful decomposition products can develop. Precautions should be taken to eliminate the vapours, e.g. by using a suitable ventilation system.

Application techniques

Especially when PUR hot melt adhesives are used, it is important that the application devices (particularly those devices fitted with nozzles), be thoroughly cleaned when there is a stoppage in the application process, (e.g. overnight or at the weekend)

Thorough cleaning can easily be performed by melting and flushing Cleaning Agent 761.6 through the application device.

Attention!

Before PUR hot melt adhesives are used in these machines again, Cleaning Agent 761.6 has to be completely drained off.

Packaging

Paper bag, 20 kg net
Box containing 12 aluminium cartridges, 0,25 kg net
Box containing 4 pouches, 1,5 kg net each
Special metal pail, 15 kg net

Storage

KLEIBERIT Cleaning Agent 761.6 can be stored for approximately 1 year.
Keep in a cool and dry place.

EX0200



KLEIBERIT®

KLEBSTOFFE • ADHESIVES

Waste Disposal

Disposal of contents and/or containers should comply with all applicable federal, state and local regulations.

Our containers are made of recyclable material.

Service

Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation.